

**316/L COIL LENGTHS**

**Weight Factor (316L): 10.93**

Nominal				Min Coil Length (ft & m)						
Outer Diameter		Wall		100 LB		200 LB		300 LB		Lbs./ft
(in.)	(mm)	(in.)	(mm)	(ft)	(m)	(ft)	(m)	(ft)	(m)	
0.125	3.18	0.020	0.50	4080	1243	8170	2490	12260	3736	0.023
0.125	3.18	0.028	0.70	3130	954	6260	1908	9400	2865	0.030
0.125	3.18	0.035	0.90	2680	816	5370	1636	8050	2453	0.035
0.158	4.00	0.039	1.00	1840	560	3680	1121	5520	1682	0.051
0.188	4.75	0.020	0.50	2540	774	5080	1548	7620	2322	0.037
0.188	4.75	0.028	0.70	1910	582	3830	1167	5750	1752	0.049
0.188	4.75	0.035	0.90	1590	484	3180	969	4770	1453	0.059
0.188	4.75	0.049	1.25	1250	381	2500	762	3760	1146	0.075
0.188	4.75	0.065	1.65	1060	323	2130	649	3200	975	0.088
0.236	6.00	0.030	0.75	1380	420	2760	841	4140	1261	0.068
0.236	6.00	0.035	0.90	1220	371	2440	743	3660	1115	0.077
0.236	6.00	0.039	1.00	1110	338	2230	679	3350	1021	0.084
0.236	6.00	0.049	1.25	930	283	1860	566	2790	850	0.101
0.236	6.00	0.059	1.50	810	246	1630	496	2450	746	0.115
0.250	6.35	0.020	0.50	1840	560	3680	1121	5520	1682	0.051
0.250	6.35	0.024	0.60	1560	475	3130	954	4700	1432	0.060
0.250	6.35	0.028	0.70	1380	420	2760	841	4140	1261	0.068
0.250	6.35	0.035	0.90	1130	344	2260	688	3390	1033	0.083
0.250	6.35	0.049	1.25	870	265	1740	530	2610	795	0.108
0.250	6.35	0.065	1.65	710	216	1420	432	2130	649	0.132
0.315	8.00	0.030	0.75	1000	304	2000	609	3000	914	0.094
0.315	8.00	0.035	0.90	870	265	1740	530	2610	795	0.108
0.315	8.00	0.039	1.00	790	240	1590	484	2380	725	0.118
0.315	8.00	0.049	1.25	650	198	1310	399	1970	600	0.143
0.315	8.00	0.059	1.50	560	170	1130	344	1690	515	0.166
0.375	9.50	0.020	0.50	1180	359	2370	722	3550	1082	0.078
0.375	9.50	0.028	0.70	860	262	1720	524	2590	789	0.107
0.375	9.50	0.030	0.75	810	246	1620	493	2430	740	0.114
0.375	9.50	0.035	0.90	700	213	1410	429	2110	643	0.131
0.375	9.50	0.049	1.25	520	158	1050	320	1580	481	0.175
0.375	9.50	0.065	1.65	410	124	830	252	1250	381	0.221
0.375	9.50	0.083	2.10	340	103	690	210	1040	316	0.265
0.375	9.50	0.125	3.18	270	82	540	164	810	246	0.342
0.394	10.00	0.030	0.75	770	234	1540	469	2310	704	0.120
0.394	10.00	0.039	1.00	600	182	1210	368	1820	554	0.152
0.394	10.00	0.046	1.15	520	158	1050	320	1580	481	0.175
0.394	10.00	0.059	1.50	420	128	850	259	1270	387	0.217
0.394	10.00	0.063	1.60	400	121	810	246	1210	368	0.228
0.394	10.00	0.078	2.00	340	103	680	207	1020	310	0.270
0.4375	11.11	0.028	0.70	730	222	1460	445	2200	670	0.126
0.4375	11.11	0.035	0.90	600	182	1200	365	1800	548	0.154
0.472	12.00	0.035	0.90	550	167	1100	335	1650	502	0.168
0.472	12.00	0.039	1.00	500	152	1000	304	1500	457	0.185
0.472	12.00	0.047	1.20	420	128	840	256	1260	384	0.219
0.472	12.00	0.059	1.50	340	103	690	210	1030	313	0.267

**316/L COIL LENGTHS (Con.)**

**Weight Factor (316L): 10.93**

**Nominal**

**Min Coil Length (ft & m)**

Outer Diameter		Wall		100 LB		200 LB		300 LB		Lbs./ft
(in.)	(mm)	(in.)	(mm)	(ft)	(m)	(ft)	(m)	(ft)	(m)	
0.500	12.70	0.035	0.90	500	152	1010	307	1510	460	0.178
0.500	12.70	0.042	1.07	420	128	850	259	1270	387	0.211
0.500	12.70	0.049	1.25	370	112	740	225	1110	338	0.242
0.500	12.70	0.056	1.42	330	100	660	201	990	301	0.272
0.500	12.70	0.065	1.65	290	88	580	176	870	265	0.310
0.551	14.00	0.039	1.00	410	124	820	249	1230	374	0.219
0.551	14.00	0.059	1.50	280	85	560	170	840	256	0.318
0.562	14.27	0.049	1.25	320	97	650	198	980	298	0.275
0.590	15.00	0.039	1.00	380	115	760	231	1140	347	0.235
0.590	15.00	0.059	1.50	260	79	520	158	780	237	0.343
0.625	15.88	0.035	0.90	390	118	790	240	1190	362	0.226
0.625	15.88	0.049	1.25	290	88	580	176	870	265	0.309
0.625	15.88	0.056	1.42	250	76	510	155	770	234	0.349
0.625	15.88	0.059	1.50	240	73	490	149	730	222	0.365
0.625	15.88	0.065	1.65	220	67	450	137	670	204	0.398
0.625	15.88	0.083	2.10	180	54	360	109	540	164	0.492
0.708	18.00	0.059	1.50	210	64	420	128	640	195	0.419
0.708	18.00	0.098	2.50	130	39	270	82	410	124	0.654
0.750	19.00	0.049	1.25	230	70	470	143	710	216	0.376
0.750	19.00	0.065	1.65	180	54	360	109	550	167	0.487
0.750	19.00	0.083	2.10	140	42	290	88	440	134	0.606
0.750	19.00	0.095	2.41	130	39	260	79	390	118	0.681
0.750	19.00	0.103	2.62	120	36	240	73	370	112	0.729